



# Demon International Ltd

## Tornado P4 & D1 Range After Service Checklist



Description	6	12	Comments
Relief valve pressure			
Leaks from pump			
Leaks from relief valve			
Operation of pump correct			
Chemical system low pressure			
Condition of hose			
Condition of lance			
Engine speed			
Max pressure			Reading
Overheat valve			
Easy start valve			
Fuel solenoid for correct operation			
Battery condition			
Clean and check battery terminals			
Inspection of fuel tank			
Drain and clean carb bowl (petrol engines)			

Items changed	Replaced	Part No	6 month	12 month
HP Seals		ARKIT1857		*
Relief valve seals		ARKIT2611		*
Relief valve piston		AR1560220		*
Relief valve tube		AR1080831		*
HP valves		ARKIT1828		*
Pump oil			*	*
Engine oil				
Gearbox oil				
Air filter (petrol engines)		HONDA001	*	*
Air filter (diesel engines)		YAN114650-125901		*
Fuel filter		YAN55120	*	*
Spark plug		HONDA004		
HP nozzle		N26001 2505	*	*
Detergent pipes		DEM10115 (per metre)	*	*
Seal Carriers x 3		AR1380090	*	*

<b>Serial Number</b>			
<b>Machine Model</b>		<b>Signed</b>	
<b>Date of Service</b>		<b>Printed</b>	